



PFEIFER

Product Catalog Elevator Technology

DRAKO Elevator Products

- For standard and special installations
- For mid- and high-rise
- For low D/d-ratios
- For compensation



Welcome dear readers,

we are pleased to present you the latest DRAKO catalog of our elevator rope products – a revised collection of technical solutions, that create reliable connections in your elevator system.

In our fast-paced world, where trust and consistency are crucial, we have decided to put our company mission "**We build connections you can count on**" at the heart of everything we do. We don't just want to make ropes; we want to create connections that last – connections you can count on – in your projects and visions.

This revised edition serves the purpose of reflecting our mission piece by piece. You will notice that this brochure has received a modern facelift. While not a complete reprint, the revised design represents our new corporate image – a visual representation of our timeless mission.

We would like to invite you to dive into the world of DRAKO elevator ropes, enrich your projects with connections, and create a future together you can rely on.

Thank you for your trust in PFEIFER and in our traditional DRAKO product brand.



DRAKO **The PFEIFER Rope Brand** for reliable connections

At the production site in Mülheim a. d. Ruhr, in the heart of the Ruhr area, PFEIFER has been producing and developing special ropes under the DRAKO product brand for elevator construction for more than 200 years.

With a sales network and companies on almost every continent, DRAKO special ropes are in use all over the world, wherever things have to move safely and reliably upwards. From Moscow to Kuala Lumpur, from New York to Hongkong and of course in Paris, London and Frankfurt we build on long-term and reliable relationships with the most demanding rope customers. Elevator manufacturers all over the world trust us as a reliable partner.

For us, tradition and innovation are on an equal footing; one is nothing without the other. Our specialist knowledge and the further development of our ropes are always at the cutting edge of technology. For this purpose, we have been working intensively with universities and institutes for a long time.

The rational and precise production of serial products and processing of individual customer-specific projects are regulated in accordance with our quality management system and certified via all relevant DIN EN ISO standards. In 2022 we were also awarded the ECOVADIS Bronze Award.



We define PFEIFER as a dynamic and open-minded company. Up-to-date technical know-how and high-quality materials are used in each of our products.

Your advantages

- ✓ Special wire ropes for your application
- ✓ Proven strand design and versatile adaptability
- ✓ Long service life
- ✓ DRAKO made fibre core, constant quality
- ✓ Low elastic and permanent elongation
- ✓ Weight compensating chains at different degrees of weight
- ✓ Weight compensating chains with various loop sizes
- ✓ Machine-welded chain links
- ✓ Inductive wear testing
- ✓ Possible since there are no fillers in the coating
- ✓ Smart accessories for easier installation
- ✓ Low maintenance costs
- ✓ 100 % rope quality, high quality assurance
- ✓ Fair benefit-cost ratio
- ✓ Highly qualified and experienced staff
- ✓ Competent advice
- ✓ Reliable service
- ✓ Worldwide sales network



Elevator technology

Imprint

Issue

10/2023

Publisher

PFEIFER DRAKO Drahtseilwerk GmbH
Rheinstraße 19–23
45478 Mülheim an der Ruhr
Germany

Management

Carlos Carranza, Heiko Stähle,
Alexander Zanocco

Information about the edition

All information in our catalogs is subject to change by PFEIFER in line with technical developments.

Model and product claims cannot be asserted. All product information and data as well as information on availability correspond to the date of printing.

Technical values from old catalogs lose their validity with this catalog.

The standards listed in the catalog in the catalog are those valid at the time of printing.

Reprints, reproductions and other distribution of pages from this catalog (with the exception of our order forms) are only permitted with our explicit, written permission.

Content

General Information about Wire Ropes

About wire ropes	3
Definitions, Designation and Classification	3
Elevator Rope Construction	5
Direction of Lay, Lay Length	6
Strand Constructions	7
Contact between Rope and Groove	8
Quality, Ropes from the same Batch, Testing	8
Tolerances of Rope Diameter	9
Discard Criteria	10

DRAKO Elevator Ropes

Ropes for Traction Sheave Elevators

Steel Core Ropes (IWRC), DRAKO 300 T / 300 TX, DRAKO 375 T	11
Double-Parallel Steel Core Ropes, DRAKO 300 TP	14
Steel Core Ropes (IWRC), DRAKO 250 T	15
Ropes with Steel and Fibre Core, DRAKO 210 TFS, DRAKO 210 TF	16
Ropes with Fibre Core (FC), DRAKO 8 x 19 NFC	17

Ropes for Roped Hydraulic Elevators

With Steel Core (IWRC), DRAKO 250 H	18
-------------------------------------------	----

Overspeed Governor (Governor Ropes)

Steel ropes, DRAKO 6 x 19 – WSC, DRAKO 250 T, 300 T	19
Ropes with Fibre Core, DRAKO 6 x 19 / 8 x 19 – FC – IWRC	20

Accessories

Maintenance of Ropes	21
Weight Watcher MSM12, DRAKO RLU (DRAKO Relubrication Unit)	22

Rope Terminations

Ferrule secured Thimble with Eye Bolt	23
Swaged Fitting with Thread	24
Symmetric Wedge Socket with Eye Bolt	25
Asymmetric Wedge Socket with Eye Bolt	26
Eye Bolts, Wire Rope Grips	27
Springs for Rope Terminations	28
Elastomer Spring Buffers for Rope Terminations	28

Compensation

Compensation for Elevator Suspension Rope Weight	29
Special Compensating Ropes, DRAKO 180 B / 200 B	31

Compensating Chains

DRAKO comfortBalance	32
DRAKO widerloopChain	33

Installation Kits	34
Roller Guides	35
Installation Material	36

Our Services

General Service	37
Ways of dispatch	38
Warnings	38
Order form	39
Delivery program	41

We are here for you!

Phone

+49 208 429010

E-Mail

info.pmh@pfeifer.de

Web

drako.pfeifer.info

LinkedIn

[linkedin.com/showcase/
ropes-services](https://www.linkedin.com/showcase/ropes-services)



Production site and logistics location on Rheinstraße, in Mülheim an der Ruhr.

Explanation of Symbols

For easy use and description of rope properties pictograms with the following meanings are used:



Characteristics



Rope grades



Elastic elongation

According to internal PFEIFER measuring method ETM 04/2017



Permanent elongation

According to internal PFEIFER measuring method ETM 04/2017



Rope diameter tolerance

Information about wire ropes

Definitions, Designation and Classification

The European Rope Standards EN 12385-1 (General Requirements), EN 12385-2 (with the above title) and EN 12385-5 (Stranded Ropes for Lifts) include rope designation with symbols laid down in EN 12385-2.

These symbols are the same for all European deliveries (see below):

Symbols for rope cores

- FC** Fibre core
- NFC** Natural fibre core
- SFC** Synthetic fibre core
- IWRC** Independent wire rope core
- PWRC** Parallel laid fullsteel rope

Symbols for strand construction

- S** Strand construction Seale
- W** Strand construction Warrington
- F** Strand construction Filler or Filler wire
- WS** Strand construction Warrington-Seale
- M** Strand construction Crosslay

Our special ropes can be ordered with their brand name, f.i. DRAKO 300 T.

Rope class

So far each rope construction is governed by rope standards. In the recent rope standards similar rope constructions in so-called rope class are summarised, e.g. the rope constructions 6 x 19 Seale, 6 x 19 Warrington and 6 x 19 Filler in the rope grade 6 x 19. The rope standards contain tables with the technical data of the common rope grade.

Rope tensile strength grade

For ropes acc. to EN 12385-5 the rope grade addresses the nominal tensile strength grades of the outer and inner wires of the rope. Additionally, the rope grade defines the minimum breaking strength of this rope. Rope grade 1570 (without the unit N/mm²) means, that all wires of this rope are of the nominal tensile strength grade 1570 N/mm².

Rope grade 1370/1770 means, that this is a dual tensile rope (term of ISO 4344) and that the outer wires of the outer strands are of 1370 N/mm² and the inner wires of the rope are of 1770 N/mm² nominal tensile strength grade.



These symbols have to be used for the standardized rope designation in the rope certificate

Example

Nominal rope \varnothing 13 mm 13 8 x 19 S NFC 1370/1770 U sZ

8 strands

19 wires per strand

Strand construction Seale

Natural fibre core

Rope grade

Here dual tensile
Outer wires 1370 N/mm²
Inner wires 1770 N/mm²

Wire finish: bright

Lay: ordinary lay right hand

Symbols for wire finish

- U** Bright (from uncoated)
- B** Galvanized acc. class B

Schlagarten

- sZ** Right hand ordinary (or regular) lay
- zS** Left hand ordinary (or regular) lay
- zZ** Right hand lang lay
- sS** Left hand lang lay

Elevator Rope Construction

Elevator Ropes


All DRAKO elevator ropes are PFEIFER-made. Ropes with fibre core can easily be identified by the DRAKO-identification label (orange coloured synthetic filament in the fibre core).

Strands

Strands consist of one or more layers of wire, which are closed in a helix around the centre wire.

Wires

Wires for elevator ropes generally have to meet different requirements than conventional ones (e.g. for crane ropes etc.). Therefore we order only wires from wire mills nearby, which are familiar with our requirements regarding the wire quality for many years.



Nominal tensile strength grade of wires

The nominal tensile strength grade in Germany is usually 1570 N/mm².

Reasonably, the international standard for lift ropes, ISO 4344 as well as the USA, Japan and many European countries know and use elevator ropes of dual tensile rope grade. To come along with sheaves of low hardness, the outer wires are then of lower tensile strength grade.

PFEIFER produces for the very different requirements of German and foreign customers ropes in dual tensile rope grade with a variety of tensile strength combinations. Ropes for roped hydraulic elevators are preferably supplied with rope grade 1770.

Cores


Two types of cores are used in the elevator industry depending on the application: The **fibre core**, made of natural or synthetic fibre, and the **steel wire core**, i. e. an independent wire rope core (IWRC).

Because of their elasticity, ropes with fibre core adapt themselves within certain limits to the shape of the corresponding groove. Natural fibre cores (made of sisal-yarn) have a better storage capacity for the lubricant than synthetic fibre cores. But in any case, the lubricant in the fibre core is only sufficient for the lubrication and impregnation of the fibre core itself.

We produce the most fibre cores for our elevator ropes in our own factory, the only way, to fulfil the high requirements of our works standard in regard to uniformity and stable lubricant content.

Synthetic fibre cores offer the advantage of an exactness in diameter and form-stability and are also rot resistant in humid environs.


The IWRCs increase the metallic cross section and thereby reduce the tensile stress in each individual wire. Consequently ropes with a steel wire core show a reduced stretch under the same load conditions compared to ropes with fibre core.



Direction of lay

Only in very special cases – f.i. unguided or only wire guided counter-weight – it should be considered to take right and left hand lay ropes.

The influence of the rope torque on the guiding forces of normal elevators with guide rails is extremely small. It should be much more important to have a set of ropes out of one production length (left hand and right hand can't be out of one production run).



Lay length

The lay length, f.i. mentioned on page 10, is described as follows:


Lay length is the distance (H) parallel to the longitudinal rope axis in which an outer strand makes a complete turn (or helix) about the axis of the rope.

Strand constructions

Here are information why certain strand and rope constructions are better qualified for specific applications in elevators.

For more detailed information about ropes and rope handling please see our technical brochure "Steel Wire Ropes in Elevators". Please ask for it or look at


drako.pfeifer.info



Seale

The most common strand construction for elevator ropes worldwide is Seale (1-9-9). This has at least the following reason:


Elevator ropes are known to get abrasion in usage and the big outer wires of Seale have a big metallic cross section to be abraded before the wires will break.



Warrington

Whenever a comparison of fatigue bending life of ropes on sheaves with round groove is made, ropes of Warrington strands are beating Seale ropes with 20 to 40 % more lifetime. The Warrington strand consists of a larger number and thinner outer wires than the Seale strand.


It must be taken into account that in elevators here is not only abrasion but also a lot of fatigue bending. Especially in elevators with double wrap drives or in roped hydraulic elevators the latter is more important.



Filler (Filler wire construction)

Filler wire strand construction is an especially fatigue bending withstanding wire configuration. This is covered by the fact that f. i. the rope 8 x 21 Filler wire + fibre core (strand) is part of the Canadian elevator rope standard. Suspension ropes, bigger in diameter than 16 mm (5/8") with 6 to 9 outer strands should have at least Filler wire strands because of higher flexibility. This especially refers to 6-strand ropes.

The disadvantages of this strand construction are: very vulnerable to geometry distortion, especially, when the Filler wire itself has not the nominal diameter. So the recommendation is given not to take Filler wire strands for ropes below 10 mm diameter.




Warrington-Seale

Ropes of Warrington-Seale construction are normally not suitable for suspension and governor ropes. But compensating ropes up from 24 mm and suspension ropes up from 22 mm are not flexible enough with the accustomed strand constructions. This is reason enough for DRAKO to recommend beyond these limits Warrington-Seale constructions with more than just 25 wires.

Contact between rope and groove

Ropes are not a plain rod with a circular cross-section; in fact they appear to be of polygonal cross section. Therefore the ropes touch the groove only at individual points. It can be only an advantage for the interaction of rope and groove, when the rope has more than 6 strands.

The success of our 9-strand DRAKO 300 T rope provides the evidence for this theory.



Quality

As we are specialized on the production of elevator ropes, we are accustomed to produce these ropes in big production lengths on special production lines with a very experienced staff of workers. This is one of the reasons for the high and equal level of DRAKO elevator rope quality.

Ropes from the same batch

We recommend to have all ropes from the same production run (batch) to achieve the best possible performance of a rope set in an elevator. Replacing single ropes of a rope set has to be avoided.



100% testing

All elevator ropes run through a testing procedure, which was developed especially for DRAKO elevator ropes. Here they are checked in whole length continuously in respect of diameter, of irregularities in material and closing. By this it is ensured that every production length corresponds to the special requirements of the PFEIFER quality standard.

Tolerances of rope diameter

The tolerances of elevator rope diameters have to be much smaller than for other ropes. The reason for this smaller tolerances is to ensure the exact fit between the rope and the sheave groove to obtain enough traction but also to achieve best durability of rope and sheave.

According to EN 12385-5 and ISO 4344 the following standard diameter tolerances are valid for elevator ropes

Rope construction				Rope diameter tolerance in % of nominal rope diameter		
Application	Core type	Rope grade	Nominal rope diameter in mm	Minimum	Maximum	
					Loaded with 5% F_{min}^*	Loaded with 10% F_{min}^*
Traction drive ropes Governor ropes	Fibre core	6 x 19 – FC 8 x 19 – FC	≤ 10	6	1	0
			> 10	5	1	0
	Steel core	6 x 19 – IWRC 8 x 19 – IWRC 9 x 19 – IWRC	≤ 10	3	0	-1
			> 10	2	0	-1

* F_{min} = Minimum breaking strength of the rope

Rope construction				Rope diameter tolerance in % of nominal rope diameter	
Application	Core type	Rope grade	Nominal rope diameter in mm	Minimum	Maximum
Ropes for roped hydraulic elevators and compensating ropes	Fibre core	6 x 19 – FC 6 x 36 – FC 8 x 19 – FC	≤ 8	0	6
			> 8	0	5
	Steel core	6 x 19 – IWRC 8 x 19 – IWRC 9 x 19 – IWRC			

This shows, that the diameter tolerances of DRAKO elevator ropes are equal to or smaller than those of the European Standard EN 12385-5, especially, the international norm ISO 4344.

The observation of an exact rope diameter has a considerable influence on the service life of an elevator rope.

For traction elevators the following facts are valid: The service life of the rope becomes the greater,

- 1. the better rope diameter and sheave radius conform with each other,**
- 2. the fewer the rope diameter decreases during operation,**
- 3. the more uniform the rope diameter remains over the whole rope length of an elevator.**

The points 1 to 3 are valid for U-grooves, point 2 and 3 also for V-grooves. A set of ropes is to be taken from the same production length.

Discard criteria

Discard criteria according to the elevator rope standards EN 12385-5 and ISO 4344 and extended based on DIN 15020.

Criteria	Discard or examination within the time span prescribed by an expert			Immediate discard		
	Rope grade 6 x 19	Rope grade 8 x 19	Rope grade 9 x 19	Rope grade 6 x 19	Rope grade 8 x 19	Rope grade 9 x 19
Average number of wire break among outer strands	> 12 per length of lay	> 15 per length of lay	> 17 per length of lay	> 24 per length of lay	> 30 per length of lay	> 34 per length of lay
Number of wire break predominantly in one or two strands	> 6 per length of lay	> 8 per length of lay	> 9 per length of lay	> 8 per length of lay	> 10 per length of lay	> 11 per length of lay
Number of wire break adjacent to another in one outer strand	4	4	6	> 4	> 4	> 6
Intermediate wire break (Valley breaks)	1 per length of lay	1 per length of lay	1 per length of lay	> 1 per length of lay	> 1 per length of lay	> 1 per length of lay

For comparison the discard criteria of the current standards

Rope construction	Number of wire in outer strands	Number of broken wire within a length of 6 x Ø	Number of broken wires within a length of 30 x Ø
DRAKO 6 x 19 S – FC	114	6	-
DRAKO 6 x 19 W – FC			
DRAKO 6 x 25 F – FC	114	10	-
DRAKO 180 B (in 6 x 25 F – FC)			
DRAKO 8 x 19 S – FC	152	13	19
DRAKO 250 H, 8.0 mm			
DRAKO 8 x 19 W – FC	152	13	26
DRAKO 8 x 25 F – FC			
DRAKO 250 T			
DRAKO 250 H (except 8.0 mm)			
DRAKO 200 B			
DRAKO 300 T, 8.0 mm	171	14	25
DRAKO 300 T (except 8.0 mm)	> 180	16	32
DRAKO 180 B (in 6 x 36 WS – FC)	216	18	35

The table above indicates whether a rope is to be replaced, based on the number of broken wires in the rope section with the highest number of such fractions. The reference length is 6 x or 30 x the rope diameter. The table complies with the specification of the EN 81-20/-50. The values apply only under the following conditions:

- The ropes are single layer regular lay ropes (the steel core is not considered a strand layer)
- The friction sheave is of cast iron or steel (for traction drive elevators)
- The broken wires are distributed evenly across the majority of the strands

Reduction in rope diameter

The ropes should be replaced if the rope diameter is reduced by more than 6 % based on a rope nominal diameter.

Please note

- If wire fractures don't occur in a regular pattern across the majority of the strands but are concentrated in one or two strands, the above table is not applicable.
- Such ropes must be replaced, if there are 5 or more broken wires adjacent to each other within one strand.
- Ropes with excessive crown wear tend to show rapidly increasing numbers of broken wires

Under certain circumstances and depending on the operating conditions, the machine design and the loads, etc., ropes might have to be replaced, even if there are no visible broken wires at the outer strands: ropes with a diameter reduction of more than 6 % (from nominal diameter) even in only a short section must be immediately removed. If the elevator system contains plastic sheaves, refer to German safety instructions for elevators 'SR Kunststoffrollen', as ropes in such systems could show internal rather than external wire fractures. The above table is to be seen only as a guideline for rope inspection and the decision for rope discard. Please note that the above figures are never to be considered the only criteria for rope discard. Any detected changes in the rope must be taken into account when assessing a rope. The final decision to remove a rope must be made on the basis of the experience of the assessing person.

For DRAKO ropes installed in systems outside Germany, the relevant statutory regulations for rope replacement apply, please look to EN 12385-3 Annex C also.

Ropes for Traction Sheave Elevators • Steel Core Ropes (IWRC)

DRAKO 300 T and 300 TX

9-strand heavy duty rope



Characteristics

Preformed, prestretched, bright (galvanized on request, in some diameters ex stock)



Rope grades

1570 and 1960
as DRAKO 300 TX



Elastic elongation

≤ 0,11 %



Permanent elongation

≤ 0,21 %



Rope diameter tolerance

See page 9



Advantages

✓ Many thin wires, hence very flexible with good bending performance

✓ Very round cross section

✓ High flexural performance

✓ Small elastic and plastic elongation

✓ Marking line for an easy installation

Field of application

DRAKO 300 T is the most efficient solution as suspension rope for high and very high elevators and for traction drive elevators with a larger number of deflection sheaves.


The strand construction of DRAKO 300 T and 300 TX is dependent on the rope diameter to optimize fatigue bending performance and wear resistance

This rope has been probably the first elevator rope in the world with a steel core (IWRC). It has been designed in 1955 by PFEIFER. After this rope being nationally and internationally successful in demanding building projects, ropes with steel core are now also implemented in the relevant European and ISO-standards.


Standard wire strength will soon reach the height limit in the challenge of the highest elevator shafts. Increasing the tensile strength of the rope wires can be a feasible way to shift this limit further. For example as 300 TX with nominal wire strength of 1960 N/mm² the rope offers new advantages to high and super high rise applications. The number of ropes, and thereby the rope mass, could be reduced in many hoist ways. Invest and installation costs can thus be reduced and weight savings in rope mass enable a sustainable reduction of the power consumption.

DRAKO 300 T and 300 TX


9-strand heavy duty rope




9 x 19 S – IWRC



9 x 21 F – IWRC



9 x 25 F – IWRC



9 x 26 WS – IWRC

Nom. Rope-Ø	Minimum breaking strenght F_{min}		Length mass approx. kg/100 m	Metallic cross section approx. mm ²
	1570	1960**		
8.0	42.1 kN	-	26.1	30.8
9.0	53.3 kN	-	33.1	39.0
9.5	59.4 kN	-	36.8	43.5

10.0	66.0 kN	-	42.8	49.7
11.0	79.9 kN	-	51.8	60.1
12.0	95.1 kN	-	61.6	71.6
12.7	106.0 kN*	-	68.0	78.9
13.0	111.6 kN	-	72.3	84.0

14.0	133.0 kN	-	84.0	96.6
15.0	153.0 kN	-	96.0	110.9
15.5	163.0 kN*	-	103.0	118.4
16.0	174.0 kN	-	110.0	126.2
17.5	208.0 kN*	-	131.0	151.0
18.0	220.0 kN*	-	139.0	159.7
19.0	245.0 kN	298.0*	154.0	178.0
20.0	272.0 kN*	-	171.0	197.2
22.0	333.0 kN*	390.0*	215.0	243.5

* No stock material

** DRAKO 300 TX not covered by recent standards for suspension ropes, upon request

Ropes for Traction Sheave Elevator • Steel Core Ropes (IWRC)

DRAKO 375 T

Remarkably enhanced E-Modulus, 9-strand heavy duty rope



Characteristics

Preformed, prestretched, bright



Rope grades

1570



Permanent elongation

≤ 0,18 %



Rope diameter tolerance

See page 9




Advantages

- ✓ E-Modulus ≥ 75,000 MPa between SF16 and SF24 measured according to DRAKO-ETM-04.2017
- ✓ Enhanced elongation behaviour compared to DRAKO 300T (E-Modulus ≥ 50,000 MPa between SF16 and SF24 measured according to method ETM-04.2017)
- ✓ Enables highest stopping precision during loading and unloading
- ✓ Reliable IWRC-design
- ✓ Marking line for an easy installation
- ✓ Very round rope cross section
- ✓ Very good fatigue bending characteristics
- ✓ Extreme wear-resistance
- ✓ 100 % quality controlled

Field of application

High rise and super high rise elevators.



9 x 19 – IWRC

Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1570	approx. kg/100 m	approx. mm ²
10.0	66.0 kN	42.8	49.7
11.0	79.9 kN	51.8	60.1
13.0	111.6 kN	73.3	84.0
15.0	153.0 kN	96.0	112.6
16.0	174.0 kN	110.0	126.2
19.0	245.0 kN	154.0	178.0

Ropes for Traction Sheave Elevators • Double-Parallel Steel Core Ropes

DRAKO 300 TP

9-strand double-parallel steel core rope



Characteristics
Preformed, prestretched,
bright



Rope grades
1570



Elastic elongation
≤ 0,10 %



Permanent elongation
≤ 0,20 %



**Rope diameter
tolerance**
See page 9



Advantages


- ✓ Well-rounded rope cross section
- ✓ Very high flexural performance
- ✓ High cross-stability
- ✓ Very low elastic and plastic elongation
- ✓ High breaking strength
- ✓ Marking line for an easy installation

Field of application

Suitable for elevator systems with high demands on precision stopping for loading and unloading procedures.

This is the strand design of the time-proven DRAKO 300 T, here with a double-parallel rope.

The wide metallic cross section leads to higher breaking strengths and reduced elastic and permanent elongation. The simplified stranding process with double-parallel ropes leads to a different rope behaviour during installation compared to independently stranded IWRC ropes.



Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1570	approx. kg/100 m	approx. mm ²
12.0*	101.0 kN	62.7	73.9
13.0*	119.0 kN	74.8	86.6
16.0*	180.0 kN	113.0	131.0
19.0*	254.0 kN	159.0	187.0
22.0*	340.0 kN	213.0	246.0

* No stock material

Ropes for Traction Sheave Elevators • Steel Core Ropes (IWRC)

DRAKO 250 T

8-strand steel core rope



Characteristics

Preformed, prestretched, bright, right hand, ordinary lay



Rope grades

1570 and 1770



Epastic elongation

≤ 0,12 %



Permanent elongation

≤ 0,22 %



Rope diameter tolerance

See page 9



Advantages

- ✓ Flexible with good bending endurance
- ✓ Low elastic and plastic elongation
- ✓ High breaking strength in relation to diameter
- ✓ Marking line for an easy installation

Field of application

Customer-focussed and cost optimized solution for individually designed and more frequented elevators.

Extended application range


With the aid of our TÜV Süd certificate concerning the examination of conformity CA067 is the application of wire ropes $\varnothing \leq 8$ mm with reduced D-/d-ratio possible.

In million ways established steel core rope with 8 outer strands in Warrington design also with smaller rope diameters. By numerous testing and verification of safety now approved for very low D/d ratio! Also suitable for indirect hydraulic elevators according to EN 81.

TÜV Süd Certificate CA067 (Ø 6.0 – 8.0 mm)

- Very low D/d ratio of up to 8.0 mm in diameter
- Required drive torque is greatly reduced
- Cost saving drives possible
- Space saving in indirect hydraulic elevators thanks to very small pulleys

So customized elevator systems with an optimized cost benefit ratio are possible.



Nom. Rope-Ø	Minimum breaking strength F_{min}		Length mass approx. kg/100 m	Metallischer Querschnitt approx. mm ²
	1570	1770		
mm	1570	1770	approx. kg/100 m	approx. mm ²
6.0	-	26.8 kN	16.4	18.5
6.5	-	31.5 kN	17.9	20.6
8.0	43.3 kN	-	27.3	31.6
9.0	54.8 kN	-	34.3	40.0
10.0	67.7 kN	-	42.3	49.4
11.0	81.9 kN	-	51.2	59.7
12.0	97.4 kN	-	61.0	71.1
13.0	114.0 kN	-	71.5	83.4
16.0	173.0 kN	-	108.3	126.0

Ropes for Traction Sheave Elevators with Steel and Fibre Core

DRAKO 210 TFS

8-strand steel and fibre core



Characteristics

Preformed, prestretched, bright, right hand, ordinary lay



Rope grades

1570



Elastic elongation

≤ 0,15 %



Permanent elongation

≤ 0,26 %



Rope diameter tolerance

See page 9


Advantages

- ✓ High breaking strength in relation to diameter
- ✓ Slightly more deformable cross section
- ✓ Good flexural performance with small deflections
- ✓ Low permanent and elastic elongation
- ✓ Marking line for an easy installation

Field of application

A special suspension rope for regularly frequented elevator systems.

Steel rope with 8 outer strands and combined steel and fibre core. Thanks to that combined core, this special suspension rope offers enhanced cross-elasticity to adapt to unique groove requirements and slightly worn grooves. The fibre core also provides additional storage space for lubricant.



Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1570	approx. kg/100 m	approx. mm ²
8.0*	38.7 kN	25.0	27.9
10.0*	60.5 kN	40.0	43.6
13.0*	102.2 kN	67.0	73.7
16.0*	154.9 kN	100.0	113.5

* No stock material

DRAKO 210 TF

Advantages

- ✓ High breaking strength in relation to diameter
- ✓ Very good flexural performance
- ✓ Marking line for an easy installation



Characteristics

Preformed, prestretched,



Rope grades

1570



Rope diameter tolerance

See page 9



Permanent elongation

≤ 0,26 %




Elastic elongation

≤ 0,15 %

A special rope for regularly frequented elevator systems

Steel rope with 8 outer strands and combined steel and fibre core. The fibre core also provides additional storage space for lubricant.



Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1570	approx. kg/100 m	approx. mm ²
8.0	40.0 kN	24.0	28.1
10.0	61.3 kN	37.8	44.7
11.0	76.1 kN	48.2	55.2

Ropes for Traction Sheave Elevators **with Fibre Core (FC)**

DRAKO 8 x 19 NFC

8-strand suspension ropes with natural fibre core



Characteristics

Preformed, prestretched, bright, right hand, ordinary lay, lang lay on request



Rope grades

N/mm²
1570 and 1370/1770



Elastic elongation

≤ 0,20 %



Permanent elongation

≤ 0,36 %



Rope diameter tolerance

See page 9


Advantages

- ✓ Thinner wires than a 6-strand rope of the same design, i.e. the rope is not as rigid and has good fatigue bending properties
- ✓ Rope is adaptable (due to a slightly deformable cross section) to slightly worn out grooves
- ✓ Easy to install
- ✓ Marking line for an easy installation

Field of application

The rope construction 8 x 19 Seale – NFC, see drawing, is without doubt the worldwide most common traction drive suspension rope. But also the rope construction 8 x 19 Warrington – NFC has established itself in Germany and UK due to better fatigue bending properties.

Anyway, 8-strand ropes with natural fibre core are the best solution for the conventional traction drive elevator. The rope quality of this rope construction depends on the quality of the fibres and the resulting fibre core. This is the reason, why PFEIFER is using special made fibre cores for DRAKO ropes.



DRAKO 8 x 19 S – FC

Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1570 and 1370/1770	approx. kg/100 m	approx. mm ²
8.0	30.4 kN	21.5	22.5
9.0	38.4 kN	27.3	28.4
9.5*	42.8 kN	30.4	31.7
10.0	47.4 kN	33.7	35.1
11.0	57.4 kN	40.7	42.5
12.0	68.3 kN	48.5	50.6
12.6	75.3 kN	50.4	58.3
13.0	80.2 kN	56.9	59.3
14.0	93.0 kN	66.0	68.8
15.0	107.0 kN	75.7	79.0
16.0	121.0 kN	86.1	89.9
18.0*	154.0 kN	109.0	114.0
19.0*	171.0 kN	121.0	127.0

DRAKO 8 x 19 W – FC

8.0	31.6 kN	22.2	23.4
10.0	49.4 kN	34.7	36.5
11.0	59.7 kN	42.0	44.2
12.0	71.1 kN	50.0	52.6
13.0	83.4 kN	58.6	61.7
16.0	126.0 kN	88.8	93.5

DRAKO 8 x 25 F – FC

18.0*	155.0 kN	112.0	115.0
-------	----------	-------	-------

* No stock material

Ropes for Roped Hydraulic Elevators **with Steel Core (IWRC)**

DRAKO 250 H

8-strand full steel rope



Characteristics
Preformed, prestretched, bright, right hand, ordinary lay



Rope grades
N/mm²
1770




Rope diameter tolerance
See page 9

Advantages

- ✓ Flexible, with good fatigue bending properties
- ✓ Low rope diameter reduction in loaded condition, also after long periods
- ✓ Low elastic and plastic elongation
- ✓ Rope grade 1770 leads to very high breaking strength
- ✓ Marking line for an easy installation

Field of application

Ideal for the heavy duty roped hydraulic elevator, requiring only minimum maintenance.



Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass	Metallic cross section
mm	1770	approx.kg/100 m	approx. mm ²
8.0*	46.7 kN	27.3	31.4
9.0	58.9 kN	33.5	38.6
10.0	72.7 kN	43.1	48.8
11.0	86.0 kN	51.9	60.2
13.0	126.0 kN	72.8	83.7

* 8 x 19 S - IWRC

Delivery note

Elevator ropes will be supplied with servings on both ends, if not specified otherwise.

Governor ropes (Full steel ropes)

DRAKO 6 x 19 – WSC DRAKO 250 T / DRAKO 300 T – IWRC

Special ropes for overspeed governor



Characteristics

Preformed, prestretched, bright, galvanized on request, right hand, ordinary lay



Rope grades

N/mm² 1370/1770, 1570, 1770 and 1960



Permanent elongation

DRAKO 6 x 19 W – WSC ≤ 0,20 %
DRAKO 250 T ≤ 0,21 %
DRAKO 300 T ≤ 0,21 %
6 x 19 S – IWRC ≤ 0,21 %
8 x 19 S – FC ≤ 0,36 %
6 x 19 S – FC ≤ 0,30 %
6 x 19 W – FC ≤ 0,30 %



Rope diameter tolerance

See page 9



Advantages


- ✓ Greater reliability and system availability
- ✓ Lower susceptibility to breakdown
- ✓ Reduced elongation with higher vertical rises
- ✓ Higher breaking strengths for reduced speed governor dimensions
- ✓ Length and form stability in all environments

These ropes are an essential functional element of the speed limitation process and the safety gear

Since the transmission of energy usually proceeds via friction, the lubrication of the governor rope needs to be dosed exactly. Following the introduction of safety gear also effective in ascent rides, governor ropes with greater breaking strength became more necessary and this was achieved by a wider rope diameter, by a higher rope grade and a full-steel rope design.

The fibre core of the DRAKO governor ropes is made of synthetic fibres. This leads to optimal diameter stability for smaller rope diameters. In addition, the synthetic-material fibres are damp-proof – and there is no swelling and no decomposing. Many DRAKO governor ropes are also available in the galvanized design.


6 x 19 W – WSC



DRAKO 6 x 19 W – WSC

Nom. Rope-Ø	Minimum breaking strength F _{min}				Length mass approx. kg/100 m	Metallic cross section approx. mm ²
	1370/1770	1570	1770	1960		
6.0	-	-	-	29.0 kN	15.1	17.6


DRAKO 250 T



DRAKO 250 T

6.5	-	-	31.5 kN	-	17.9	20.6
8.0	-	43.3 kN	46.6 kN	-	27.3	31.6
9.0	-	54.8 kN	-	-	34.3	40.0
10.0	-	67.7 kN	72.7 kN	-	42.3	49.4

DRAKO 300 T



DRAKO 300 T


8.0	-	42.1 kN	45.0 kN	-	26.1	30.8
9.0	-	53.3 kN	-	-	32.2	38.0
10.0	-	66.0 kN	71.0 kN	-	42.8	49.2
13.0	-	111.6 kN	118.3 kN*	-	72.3	84.0

Governor ropes (Fibre core)

DRAKO 6 x 19 / 8 x 19 – FC


Special ropes for overspeed governor

Nom. Rope-Ø	Minimum breaking strength F_{min}				Length mass approx. kg/100 m	Metallic cross section approx. mm ²
	1370/1770	1570	1770	1960		




DRAKO 8 x 19 S – FC

6.5	-	19.0 kN*	-	-	14.6	13.4
8.0	-	30.3 kN	34.2 kN	-	21.5	22.5
9.5	-	-	48.3 kN	-	30.4	31.7



DRAKO 6 x 19 S – FC

6.0	-	-	21.4 kN	-	13.0	13.8
-----	---	---	---------	---	------	------



DRAKO 6 x 19 W – FC

6.0	-	19.8 kN	-	24.7*	13.2	14.3
6.3	-	-	-	27.2	14.6	15.8
6.5	-	23.2 kN	26.2 kN	-	15.5	16.8
8.0*	35.1 kN	-	-	-	23.6	25.4

* No stock material

Delivery note

Elevator ropes will be supplied with servings on both ends, if not specified otherwise.

Maintenance of Ropes

Elevator Rope Maintenance

DRAKO elevator ropes are lubricated during the manufacture process with the aim of reducing corrosion and abrasion. But the quantity of lubricant so applied may only be enough to prevent elevators with tightly calculated traction capability from slipping.

spray can or oil can or paint brush or similar. For traction drives, only small quantities need to be applied, following which the elevator should be run up and down the whole distance several times. In doing so, observe any slipping characteristics and, if necessary, apply more lubricant. The lubricant used should initially have low viscosity and good creep properties so that the inner parts of the rope are also lubricated.

For this purpose, we recommend two DRAKO special rope lubricants: either **DRAKO LUBE** or **DRAKO SOL**, which are both compatible with the lubrication applied at manufacture. As a further alternative, **DRAKO Outdoor** has stood the test of time in use outdoors. It comes as a paste but takes on fluid form in the course of operation.

Transparent and of low viscosity, **DRAKO LUBE** and **DRAKO SOL** are able to penetrate the rope even under load. During non-operational phases, they flow back to the rope contact points from which they were displaced during rope/elevator operation.

Since, however, dust and abrasion tend to thicken the lubricant, it is only in rare cases that this first lubrication remains effective over the entire service life. And so PFEIFER recommends that the elevator ropes be periodically relubricated during service.

Relubrication is not necessary as long as your fingers pick up a smear of oil if you touch the rope. As such, relubrication is carried out a number of ways – with a



DRAKO FLUID SF, another of our recommended elevator rope lubricant, is **solvent-free** and therefore suitable for use in **automatic lubrication equipment**.

Attention: The automatic lubricators available nowadays may only be used at a specific elevator for a very limited period of time. Otherwise, excess lubrication promptly occurs with the

attendant risk of rope slip. Over lubricated ropes can be degreased by means of our special chemically neutral **DRAKO FLORIDEAL** rope degreasing powder.



Our lubricants contain solvents (except for DRAKO FLUID SF)! Only to be used in well ventilated areas.

DRAKO rope maintenance products are designed to conform to the basic lubrication that DRAKO ropes receive at manufacture. If other products are used, no warranty for conformance can be offered. This also applies to the rope maintenance products of other manufacturers.

It is imperative that you consult the information given for the use and maintenance of elevator ropes made of steel wire as per EN 12385-3.

Products and batches

Article	Condition	Application	Container size	Solvent	Application by means of
DRAKO LUBE	Fluid	Indoor and outdoor	2,5-l-can 5,0-l-can	Yes Yes	Brush/roller
DRAKO SOL¹⁾	Fluid	Indoor	Spray can 500 ml (12 can = 1 box)	Yes Yes	Spray
DRAKO FLUID SF	Fluid	Indoor and outdoor	2,5-l-can 5,0-l-can	No No	Automatic lubricator, brush/roller, squirt gun
DRAKO Outdoor	Fluid/paste	Outdoor	10-kg-can	Yes	Brush/roller
DRAKO Florideal	Rope degreasing powder	Indoor and outdoor	20-kg-bag 5-kg-pot with lid	- -	Gloves

¹⁾ Hazardous substance, observe all transport regulations!

Accessories



WeightWatcher MSM12

The right rope tension has a massive impact onto the rope lifecycle expectation

Insufficiently adjusted ropes and excessive total weights result in undesirable and premature wear. Thanks to the WeightWatcher rope load measuring system the rope adjustment and the weighing of car and counterweight becomes child's play. Due to the patented measuring principle the exact loads in each rope can be measured, within seconds, without the necessity of prior calibration with weights.

The integrated rope adjustment wizard will guide you through the rope adjustment and logs each measurement in a report that can later be manipulated on the PC. This makes the WeightWatcher the optimum tool for your service to customers.

Advantages

- ✓ Measurement of up to 12 ropes
- ✓ Measurement of single loads and total weight
- ✓ Rope tension assistant for quick cable adjustment
- ✓ Convenient menu with settings of the suspension variant, unit weight, tolerance
- ✓ Storage of complete documentation
- ✓ Color touch screen for easy operation
- ✓ Advanced lithium-ion batteries
- ✓ BlueTooth can be connected via android app with smartphones or tablets

For more information please see our leaflet **Weight Watcher**.



Supplementary mounting bracket available on request.

DRAKO RLU

The automatic relubrication device is the perfect solution for the permanent relubrication of the suspension ropes in your elevator system.

The ropes are automatically relubricated with the recommended amount of lubricant. This sustainably improves the service life of the suspension ropes. The included solvent-free lubricant **DRAKO Fluid SF** is optimally matched to the lubricants used in rope production and is 100 % compatible.

After simple installation, the required lubricant quantity is set via a selector dial. The setting recommended by PFEIFER is level 12, i.e., the lubricant quantity of 125 ml is continuously delivered to the ropes over a period of one year (see table below).




Runtime	30	90	180	270	360
MI/Day	4,17	1,39	0,69	0,46	0,35
Grade	1	3	6	9	12

Spare parts delivery

The 125 ml cartridges are easy to replace after emptying. The brushes and the cartridges can be reordered as spare parts.

Rope Terminations



Ferrule secured Thimble with Eye Bolt

How to order additional to the designation of the required rope f. i. a 13 mm rope, thimble DIN 6899 (if DIN 3090, please specify) selected eye bolt M 20, 450 mm long and spring:

One rope end with thimble and eye bolt M 20 x 450 D

Anti-Twist Rope Sets (4 mm rope with 1 wire rope grip) are available ex stock.

Please note

The elevator rope constructions shown in this catalogue have very different minimum breaking strengths. When specifying rope terminations and springs or spring buffers, their respective maximum applicable force is to be considered.

Rope terminations are to be secured against rotation.

Eye Bolts


Rope-Ød mm	Nominal size (a x L ₂)	L ₃ (approx.) mm	D mm	E (approx.) mm
6.0 - 8.0	M 12 x 260	60	26.0	50.0
	M 12 x 350	150	26.0	50.0
	M 12 x 500	150	26.0	50.0
9.0 - 11.0	M 16 x 260	120	22.0	51.4
	M 16 x 300	150	22.0	51.4
	M 16 x 350	200	22.0	51.4
	M 16 x 400	200	22.0	51.4
	M 16 x 450	200	22.0	51.4
	M 16 x 500	200	22.0	51.4
12.0 - 14.0	M 20 x 290	120	27.7	67.6
	M 20 x 450	200	27.7	67.6
	M 20 x 600	200	27.7	67.6
15.0 - 17.0	M 24 x 400	220	27.0	65.0
	M 24 x 600	200	27.0	65.0

Eye bolts will come with washer (DIN 125), 2 nuts and 1 split-pin.

Accessories

Designations	Contents
D	1 pressure spring, 2 spring collars
FP	1 elastomer spring, 1 washer
FP 2	2 elastomer springs, 1 washer
FP 3	3 elastomer springs, 1 washer

On request we supply for this kind of rope suspension a complete accessory kit (unmounted), comprising:



Swaged Fitting with Thread

This slim construction of rope termination is particularly suitable for modern concepts of machineroomless elevators.

These terminations must be secured against rotation by means of the big securing hole at the upper end of the rod and a small steel wire rope.

The small inspection hole in the swaged part of the terminal allows to control the presence of sufficient inserted rope length.

TÜV Süd has certified, on the base of researches at the Institut für Fördertechnik at the University of Stuttgart, that our system of swaged fittings fulfils the requirements of EN 81 for DRAKO-Ropes with fibre cores as well as for DRAKO-Ropes with steel core.

DRAKO swaged fittings with thread are compliance tested by TÜV Süd!

Please note

The elevator rope constructions, shown in this catalogue have very different minimum breaking strengths. When specifying springs or spring buffers, their respective maximum applicable force is to be considered.

Rope-Ø d mm	Nominal size	Thread-Ø A mm	Thread length L ₃ approx. mm	Shaft length L ₂ approx. mm	Swagged Ø B approx. ¹⁾ mm	Swagged Total length L ₁ approx. ¹⁾ mm	Securing hole Ø C mm
6.0	M 10 x 235	M 10	60	236	14.5	308	3
6.0	M 10 x 145	M 10	45	45	14.5	145	3
6.5	M 10 x 235	M 10	60	236	14.5	310	3
8.0*	M 14 x 160	M 14	160	163	16.0	240	6
8.0**	M 14 x 300	M 14	200	300	16.0	380	6
10.0*	M 16 x 160	M 16	160	163	18.0	260	8
10.0**	M 16 x 300	M 16	200	300	18.0	400	8
11.0*	M 16 x 160	M 16	160	163	20.5	270	8
11.0**	M 16 x 300	M 16	200	300	20.5	410	8
12.0*	M 16 x 160	M 16	160	163	22.5	280	8
12.0**	M 16 x 300	M 16	200	300	22.5	420	8
13.0*	M 20 x 160	M 20	160	163	24.5	280	8
13.0**	M 20 x 300	M 20	200	300	24.5	420	8
16.0*	M 24 x 160	M 24	160	163	29.0	310	8
16.0**	M 24 x 350	M 24	250	350	29.0	500	8

* Special size: when used with springs, then only with elastomer spring buffers; ** normal size


1) Provided only as information for determining installation dimensions

Symmetric Wedge Socket EN 13411-7 with Eye Bolt DIN 444

Termination acc. to EN 13411-7 in combination with our eye bolts fulfil the requirement of EN 81, to withstand at least 80 % of the minimum breaking strength even when used together with the fullsteel ropes DRAKO 250 H.

Please note

The elevator rope constructions shown in this catalogue have very different minimum breaking strengths. When specifying rope terminations and springs or spring buffers, their respective maximum applicable force is to be considered. Rope terminations are to be secured against rotation.



Rope- ø d	Nominal size socket	Normal size Type UM					Type D			Type FP			Type FP 2		Type FP 3	
		a	L ₁	L ₂ *	L ₃	Weight	d ₁	L ₄	Weight	d ₂	L ₅	Weight	L ₆	Weight	L ₇	Weight
mm			mm	mm	mm	ca. kg	mm	mm	appr. kg	mm	mm	appr. kg	mm	appr. kg	mm	appr. kg
4.0 – 5.0	5.0	M 10	276	180	70	0.420	25.0	85.5	0.510	40.0	38	0.361	55	0.373	72	0.384
5.0 – 6.5	6.5	M 10	264	180	70	0.380	25.0	85.5	0.470	40.0	38	0.401	55	0.414	72	0.424
6.0 – 8.0	8.0	M 12	450	320	150	0.780	45.0	167.0	1.420	50.0	51	0.870	79	0.900	107	0.930
9.0 – 11.0	11.0	M 16	484	320	150	1.650	45.0	173.0	2.490	58.0	59	1.785	87	1.815	115	1.850
12.0 – 14.0	14.0	M 20	598	400	150	3.230	54.0	202.0	4.500	68.0	65	3.530	93	3.570	121	3.610
15.0 – 17.0	17.0	M 24	674	450	150	5.300	65.0	248.0	8.150	80.0	74	5.830	102	5.910	130	5.990
18.0 – 20.0 ¹⁾	20.0	M 27	760	500	150	8.000	65.0	254.0	10.950	-	-	-	-	-	-	-
21.0 – 25.0 ¹⁾	25.0**	M 30	740	500	150	11.000	80.0	251.0	14.500	-	-	-	-	-	-	-

* Normal size
Different lengths L₂ see page 28 table Eye Bolts.

** Not acc. to DIN

1) On request


The socket body is galvanized.

How to order (example)

Type 14	D	x	Length L
Symm. wedge socket nominal size 14 for rope – Ø 12-14 mm	With spring		Length L ₂ of eye bolt acc. table above or acc. to the respective table page 30

Asymmetric Wedge Socket DIN 43 148 (EN 13411-6) with Eye Bolt similar DIN 444

Terminations acc. to DIN 43148 only in some combinations of rope constructions, rope diameters and eye bolts are according to the requirement of EN 81 (Requirement: withstanding at least 80 % of the rope's minimum breaking strength). Please contact us in case of any questions.



Rope- Ø d mm	Nominal size socket	Normal size Type KUM					Type KD			Type KFP			Type KFP 2		Type KFP 3	
		a	L ₁	L ₂ *	L ₃	Weight	d ₁	L ₄	Weight	d ₂	L ₅	Weight	L ₆	Weight	L ₇	Weight
6.0 – 7.0	353	M 12 ¹⁾	430	300	150	0.948	44.0	167	1.595	50.0	51	1.051	79	1.079	107	1.107
8.0	352	M 12 ¹⁾	430	300	150	0.920	44.0	167	1.567	50.0	51	1.023	79	1.051	107	1.079
9.0 – 12.0	351	M 12 ¹⁾	430	300	150	0.892	44.0	167	1.539	50.0	51	0.995	79	1.023	107	1.051
10.0 – 12.0	402	M 16	440	300	150	1.278	44.0	173	2.070	57.0	59	1.454	87	1.482	115	1.510
12.0 – 14.0	401	M 16	440	300	150	1.250	44.0	173	2.042	57.0	59	1.426	87	1.454	115	1.482
12.0 – 15.0	450	M 20 ¹⁾	590	400	150	3.330	50.0	202	4.840	68.0	65	3.620	93	3.666	121	3.712
16.0 – 20.0 ²⁾	500	M 27 ¹⁾	715	500	150	7.740	65.0	254	10.760	-	-	-	-	-	-	-

* Normal size
Different lengths L₂ on request.

- 1) Eye of bolt not acc. to DIN
2) On request

The socket body is galvanized.

How to order (example)

Type 402

KD

x

Length L


Asymm. wedge socket
nominal size 402 for
Ø 10 to 12 mm ropes

With spring

Length L₂ of eye bolt
acc. table above

Eye Bolts DIN 444

In combination with symm. wedge sockets EN 13411-7.



Thread (a)	M 10**	M 12	M 16	M 20	M 24	M 27	M 30**
d ₂	10.5	12.2	16.0	18.0	22.0	25.0	42.0
s	9.0	14.0	17.0	22.0	25.0	27.0	30.0
L ₂ / L ₃	180/70*	-	200/100	-	-	-	-
L ₂ / L ₃	130/35	-	-	-	-	-	-
L ₂ / L ₃	230/70	-	300/150	300/150	-	-	-
L ₂ / L ₃	-	320/150*	320/150*	-	-	-	-
L ₂ / L ₃	-	-	350/150	-	-	-	-
L ₂ / L ₃	-	400/150	400/150	400/150*	-	-	-
L ₂ / L ₃	-	-	450/150	450/150	450/150*	-	-
L ₂ / L ₃	-	-	500/150	-	-	500/150*	500/150*
L ₂ / L ₃	-	-	-	560/150	600/150	-	-
L ₂ / L ₃	-	-	-	-	-	800/400	-

All dimensions in mm

* Normal sizes

Sizes in bold type are usually available ex stock.

** Not acc. to DIN


Wire Rope Grips EN 13411-5

To be used with wedge sockets EN 13411-7 or DIN 43148 / EN 13411-6


Nominal size = biggest nominal rope-Ø	5.0	6.5	8.0	10.0	12.0	14.0	16.0	19.0	22.0
---------------------------------------	-----	-----	-----	------	------	------	------	------	------

For intermediate nominal rope diameters, the next bigger grip size shall be applied. Nominal size 5 is only applicable for 5 mm nominal rope diameter. Usage only acc. to the requirements for application and installation of EN 13411-5.

Standardised Fixing of Rope End with Wire Rope Grip



Symmetric wedge socket
See EN 13411-7



Asymmetric wedge socket
See EN 13411-6

Springs for Rope Terminations

Calculation of compression s


$$s = \frac{F}{c} \text{ [mm]}$$

c Spring factor [kN/mm]

F Spring load [kN]
(Same as rope load)

	Spring I	Spring II	Spring III	Spring IV	Spring V	Spring VI
Symm. wedge socket EN 13411-7	5 D 6.5 D	8 D	11 D	14 D	17 D 20 D	25 D
Asymm. wedge socket EN 13411-6/DIN 43 148	-	351 352	401 402	450	500	-
Swaged fitting	M 8 M 10	M 12	M 16	M 20	M 24	-
Wire-Ø [mm]	4.5	7.5	9.0	11.0	15.0	18.0
Outer-Ø [mm]	23.5	43.0	46.0	53.0	65.0	80.0
Average spring-Ø [mm]	19.0	35.5	37.0	42.0	50.0	62.0
Length unloaded [mm]	61.5	135.0	135.0	157.5	190.0	155.0
Maximum spring load Fmax [kN]	1.703	3.382	5.930	9.383	14.880	24.525
Compressions s [mm] at spring load Fmax	21.0	47.0	40.5	42.0	32.5	27.0
Spring factor c [kN/mm]	0.081	0.072	0.146	0.223	0.458	0.908

Elastomer Spring Buffers for Rope Terminations





Characteristics


- Grease and oil resistant
- Excellent damping properties
- Material: Cellular polyurethane-elastomer

Type	d	D ₁ *	D ₂ *	L ₁ *	L ₂ *
	mm	mm	mm	mm	mm
5.0	10.0	40	20	17	20
8.0	13.0	50	22	28	33
11.0	17.0	50	22	28	33
14.0	21.0	65	27	28	33
17.0	25.0	80	27	28	33


* Unloaded, dimension d must fit to the thread diameter a of the eye bolt





Type 5FP




Type 8FP



Type 11FP



Type 14FP



Type 17FP

Compensation for Elevator Suspension Rope Weight

Why is compensation under certain circumstances useful or even necessary?

Good reasons for weight compensation

- In high elevators, the power consumption of the electrical drive system can be minimized by rope weight compensation; alternatively, the drive system can be dimensioned for smaller loads, and the power supply to be installed can thus be reduced
- The car can be started and stopped much more smoothly, and the calculation of the approach speed of the car to the next stop is optimized
- The traction properties required for elevators with long hoistways can often only be achieved by means of weight compensation

Depending on the hoisting height, car speed and operation purpose of the elevator, chains or ropes can be used for this purpose

Standard balance chain without jacket

- For nominal speeds up to 0.6 m/s
- Disadvantage: High noise level

Balance chain with jacket, whereby the chain structure is still visible

- For nominal speeds up to 1.6 m/s e. g.

Balance chain with jacket, round cross section

- For nominal speeds up to 3.0 m/s. e. g. DRAKO CB
- For speeds from 1.75 m/s it is recommended to install balance chain guides in the lower hoistway section

In addition to above mentioned applications PFEIFER offers compensating chains which provide a bigger loop diameter. So the pressure on the car guides can substantially be reduced.

For compensating ropes there are the following differences

Untensioned balance ropes

Previously common with certain specifications (tiller ropes); the run behaviour of such ropes is however inferior to that of jacketed balance chains.

Tensioned balance ropes

According to EN 81-20 5.5.6.2, ropes used as balance ropes are to be run with tensioning sheaves. Only tensioned weight compensating ropes in conjunction with the securing devices on the tensioning sheaves as required by EN 81-20 5.5.6.1, for nominal speeds above 3.5 m/s can prevent the feared 'jumping' of the counterweight upon activation of the safety brake.

Note

Up to recently, balance ropes were produced with the same ropes construction and diameter as the suspension rope in the respective installation. PFEIFER will of course continue to supply its customers with such solutions. For high hoistways (rope oscillation!) and/or more than six suspension ropes (with the necessary intricate tensioning roller system), operators should consider the installation of less but thicker balance ropes.

Advantages of specifically designed balance ropes

PFEIFER recommends the use of specifically designed and dimensioned balance ropes of the product series DRAKO 180 B and DRAKO 200 B. These ropes feature a synthetic fibre core and, in certain cases, a strand construction that is not available for suspension ropes.



Flexibility

This construction consists of a many thin wires, making the ropes particularly flexible (minimum diameter ratio D/d for balance rope sheaves is 30 only!).




Length stability

In contrast to natural fibre cores, synthetic fibre cores don't absorb moisture from the ambient air. Elongation and contraction (that can exceed the tensioning length in the case of long ropes) as a result of fluctuating humidity are thus effectively prevented.



Special lubricant

Compensating ropes are lubricated differently and also more extensively than traction ropes, as minimum friction is not an issue. This results in a prolonged service life of the installation combined with longer servicing intervals.



Fibre core

Under certain circumstances, steel cores in compensating ropes might lead to early damage. Synthetic fibre cores however provide excellent reliability under all conditions.



Easy handling

The ropes are of preformed regular lay construction, which significantly reduces the tendency of becoming untwisted during handling and installation.



Safety factor

In respect of EN 81-20 5.5.6.3 compensation-chains and -ropes have to be able to withstand any forces acting on them with a safety factor 5.

To assess whether a rope is to be replaced, please see page <ÜS>.

Ropes for Compensation • Special Compensating Ropes

DRAKO 180 B / 200 B

Special compensating ropes for elevators to be used as tensioned balance ropes only.

**Characteristics**

Preformed, bright, right hand, ordinary lay, made with a synthetic fibre core (SFC)

**Rope grades**

1370/1770 or 1570

**Rope diameter tolerance**

See page 9




Special compensating ropes (balance ropes), to be used in tensioned application only. The rope construction varies with the nominal diameter to optimize the performance.

The purpose and the operating conditions of weight compensating ropes are different to those of traction sheaves and suspension ropes used in the same elevator systems. Which is why PFEIFER recommends the use of special compensating ropes. Abundant lubrication and a special fibre core, a selection of even wider rope diameters (for fewer ropes) and a flexible rope design adapted to the rope diameter will all go towards a longer service life, quietness of running and stability of length.

However, as always, PFEIFER can deliver compensating rope in the same design as that of the suspension rope like DRAKO 300 T.

Delivery note

Elevator ropes will be supplied with servings on both ends, if not specified otherwise.

**DRAKO 180 B**

Nom. Rope-Ø	Minimum breaking strength F_{min}	Length mass
mm	1370/1770 or 1570	approx. kg/100 m
13.0*	83.7 kN	60.7
16.0*	127.0 kN	92.0
18.0*	160.0 kN	116.0
19.0*	179.0 kN	130.0
20.0*	198.0 kN	144.0
22.0*	240.0 kN	174.0
24.0*	292.0 kN	211.0
26.0*	342.0 kN	248.0
36.0**	656.0 kN	476.0
38.0**	731.0 kN	530.0

DRAKO 200 B

13.0**	74.3 kN	57.5
16.0*	113.0 kN	87.0
19.0*	159.0 kN	123.0
22.0**	213.0 kN	165.0

* No stock material
** Upon request

Compensating Chains



DRAKO comfortBalance

Pressure-extruded,
automatically-welded chain
made of low-carbon steel

60 °C flame-retardant polyvinyl chloride that resists
oxidation, weathering, solvents and chemicals.

Field of application

Temperature range

-15 °C to +60 °C

Rated speed


≤ 3,0 m/s (acc. EN 81-20/-50)

Installation material

3 U-bolts, 1 shackle, 1 grip

Dampening device

DRAKO Roller DR-L and DR-H



Type	Unit Weight	Chain diameter	External diameter	Max. hanging length	Recom. loop diameter
	kg/m	mm	mm	m	mm
DRAKO CB 110	1.1	5.5	24	150	560
DRAKO CB 150	1.5	6.3	29	170	600
DRAKO CB 220	2.2	7.9	35	180	600
DRAKO CB 300	3.0	9.0	38	185	650
DRAKO CB 370	3.7	10.5	42	185	650
DRAKO CB 450	4.5	11.5	44	185	650
DRAKO CB 520	5.2	12.7	49	185	680
DRAKO CB 600	6.0	13.5	52	185	680

Please note

For outdoor application dampening devices are always advisable because of the influence of wind.



DRAKO widerloopChain

Pressure-extruded, automatically-welded chain made of low-carbon steel

60 °C heatproof PVC resistant to weathering, solvents and chemicals.

Field of application

Temperature range

0 °C to +60 °C

Rated speed


≤ 3,0 m/s (gem. EN 81-20/-50)

Installation material

3 U-bolts, 1 shackle, 1 grip

Dampening Device

DRAKO Roller DR-L and DR-H



Advantages

- ✓ Special PVC composition results in a distinct wider loop diameter than conventional weight compensating chains
- ✓ Permits a centred installation process under the car even
- with wide shafts and large cars
- ✓ Pressure on the car guides substantially reduced, wear-and-tear minimized
- ✓ Improved shaft efficiency

Type	Weight kg/m	Chain diameter mm	External diameter mm	Max. hanging length m	Recom. loop diameter mm
WLC 110	1.1	5.5	24	150	1000 - 1600
WLC 150	1.5	6.3	29	170	1000 - 1600
WLC 220	2.2	7.9	35	180	1000 - 1600
WLC 370	3.7	10.5	42	185	1000 - 1600
WLC 450	4.5	11.5	44	185	1000 - 1600
WLC 600	6.0	13.5	52	185	1000 - 1600

Please note

For outdoor application dampening devices are always advisable because of the influence of wind.

Installation Kits

Installation Kits for DRAKO CB / WLC

One installation kit contains the material for the installation of one balance chain.

The installation kits were specifically designed for use with DRAKO compensating chains. They guarantee safe operation.




The use of other hardware could seriously jeopardize the safety of the installation



Please note

A detailed installation manual is available. Please inquire for further information if necessary.

Kit	Content	Quantity	Dimensions			
			A (mm)	B (mm)	C (mm)	D (mm)
ICB 110	U-bolt,	3	6	120	75	50
	Shackle,	1	8	1,6 x 20	M 6 x 35	M 6
	Stainless steel grip	1	710 +/- 10	26	42	-
ICB 150	U-bolt,	3	8	120	75	50
	Shackle,	1	12	2 x 20	M 8 x 45	M 8
	Stainless steel grip	1	710 +/- 10	31	47	-
ICB 220	U-bolt,	3	10	120	75	50
	Shackle,	1	12	2,5 x 30	M 10 x 50	M 10
	Stainless steel grip	1	710 +/- 10	37	53	-
ICB 300	U-bolt,	3	10	120	75	50
	Shackle,	1	12	2,5 x 30	M 10 x 50	M 10
	Stainless steel grip	1	710 +/- 10	40	56	-
ICB 370	U-bolt,	3	12	120	75	50
	Shackle,	1	12	3,2 x 30	M 12 x 50	M 12
	Stainless steel grip	1	710 +/- 10	44	60	-
ICB 450	U-bolt,	3	12	120	75	50
	Shackle,	1	12	3,2 x 30	M 12 x 50	M 12
	Stainless steel grip	1	710 +/- 10	47	63	-
ICB 520	U-bolt,	3	14	120	75	50
	Shackle,	1	16	3,2 x 30	M 14 x 60	M 14
	Stainless steel grip	1	710 +/- 10	51	67	-
ICB 600	U-bolt,	3	14	120	75	50
	Shackle,	1	16	3,2 x 30	M 14 x 60	M 14
	Stainless steel grip	1	710 +/- 10	54	70	-



Roller guides

Roller Guide DR-L / DR-H

The DR-L and DR-H roller guides ensure that with higher ride speeds there are no vibrations in the elevator system. To select the right type, please consult the following table. It is recommended that in the case of a shaft height of over 50 m and a travel speed of over 1.75 m/s, two rollers be employed.

For shaft heights of less than 50 m and speeds of less than 1.75 m/s, the use of guides is normally not required.

The guides dampen the vibrations that can emerge as the result of high operating speeds or as the result of an emergency stop. They prevent the chain from possibly beating against the wall of the shaft. That being so, guides might be useful at lower speeds as well.



Please note

During installation, ensure that the weight compensating chain during operation will not constantly touch the roller guide unit. The chain must be centred in the middle.

It is imperative that the suspension points at the car and/or the counterweight are aligned vertically over the guide.

The table below gives a good overview of the roller guides available

Type/ Elevator Speed	DRAKO CB / WLC
1.2 to 1.75 m/s	DR-L / DR-H
1.75 to 3.0 m/s	DR-H



Installation Material

Installation Material IK-R


For Roller Guides – Mounting Bracket to be installed between Counterweight Guide Rails (IK-R)

The bracket will be fixed between the guide rails of the counterweight. Depending on the number of compensation chains installed at the counterweight, one or two dampening rollers can be installed.

A space of minimum 480 x 290 mm for one centred dampening roller is required between the guide rails. The bracket should have approx. 80 mm distance between shaft wall and counterweight guide rails. Length can be adjusted to maximum 1500 mm between the guide rails.

IK-R for DR-H mounting

Pos.	Part	Quantity
1	Rail D – 1500 mm	2
2	Rail A – 392 mm	2
3	Rail D – 392 mm	4
4	Rail nut M 10	20
5	Bolt – M 10 x 60	4
6	Beam clamp	4
7	Bolt – M 10 x 40	12
8	Spring nut M 10	4
9	Square washer	8
10	Bolt – M 10 x 25	8
11	Washer – 10,5	8
-	Installation Procedure	1



Dampening Rollers are not part of the installation material!
Installation guide for compensating chains and accessories is available at

drako.pfeifer.info


Installation Material IK-F

For Roller Guides on shaft floor – Mounting Bracket to be installed at pit floor at car side (IK-F)

The bracket will be installed at the pit floor under the car. Depending on the number of compensation chains installed at the counterweight, one or two dampening rollers can be installed.

IK-F for DR-H mounting

Pos.	Part	Quantity
1	Floor plate – 150 mm	2
2	Rail A – 1100 mm	2
3	Spring nut M 10	6
4	Angle bracket – 244 mm	2
5	Bolt M 10 x 40	6
6	Rubber plate	2
7	Bolt M 12	4
8	Bolt M 12 x 40	4
9	Washer 13	4
10	Spring Washer A12	4
11	Dowel 12	8
-	Installation Procedure	1



Our Service

General Service

Technical Support

Using the large number of technical configurations available to us, we are pleased to assist you in finding the right solution and combination for your ropes and rope accessories.

As early as the planning and design phases, we will support and advise you as extensively as possible. In addition to years of experience, we have all kinds of calculation aids for elevator rope requirements. We can help you select the best rope for your purposes, understand the rope drive and elevator system and advise you accordingly.

Rope life cycle and elongation calculation with the DRAKO Rope Calculator

A rope calculation is a complex process, with many factors to consider. Our Technical Competence Center (TCC) has gathered farreaching experience in the field of rope service life assessment and this has led to the creation of professional software. An end-user version of this sophisticated program is available which will help you greatly when it comes to the design of your system.

Further the proven DRAKO Rope Selector has been implemented into the DRAKO Rope Calculator. It helps to calculate the rope drive of your traction sheave elevator asper EN 81 and, additionally, many any significant values based on standards in place. In this way, we can assess and or modify the actual choice of rope as well as the effect of the influential components. The result: we can recommend you the best possible coordinated rope drive system.

Register free of charge at
drako-calculator.pfeifer.info

Rope and system diagnosis

Unexpected damage to rope can never be ruled out in elevator systems, and sometimes the cause cannot be established – at least at first. Our highly experienced experts will help you pinpoint the cause of damage and ensure that the same malfunction does not re-occur after the rope has been changed.

We are happy to advise you free of charge! In the case of more extensive calculations and services having to be provided, we would be pleased to make you an offer.

Simplified order form

We aim to make the selecting and ordering procedures as easy as possible. Feel free to order or to place a query at: info.pmh@pfeifer.de

Stock keeping

For your convenience, we permanently keep in stock all sizes of weight compensating chains and over 80 different rope types and diameters for elevator operations. We can respond swiftly to your delivery requirements.

Systemized deliveries / ropes and accessories from a single source

Do you need our ropes and/or compensating chains complete with accessories at the building site?

We offer tailor-made solutions for ready-packed systemized deliveries.

Response within 24 hours

If it is foreseeable that we cannot reply to your query in the desired time, we will get back to you within one workday after receipt of your message and let you know:

- Who your contact person is, and,
- By when exactly you can expect the reply you need

Test laboratory

We carry out visual inspection (wire breaks, corrosion, deformation, wear), single-wire testing, total disruption, breaking load determination, grease content determination, elongation measurement and fatigue bending test.

If required, we will gladly make you an appropriate offer.



Discover our complete range of services under

drako.pfeifer.info



Ways of dispatch



Up to a length of 50 m, elevator rope will be commissioned **in coils**, if requested, also with ferrule secured terminations. The dispatch of each commission will be effected **on pallets**, accessories loose in a bag. Larger quantities will be packed in **skeleton containers** if requested.



Production lengths will be commissioned on **wooden reels** which can be returned. These reels can also be packed (flat) on **EURO-pallets**.



Cut-to-lengths, usually commissions of more than 100 meters single length, will be dispatched on **non-returnable** reels on pallets, also with ferrule secured terminations, if requested.



Furthermore we offer the opportunity to let you have your commissions **systemized**. In this case, elevator ropes and loose rope termination material as well as other accessories and governor ropes, for example, can be packed in **stable cardboard** boxes with handles. Then the boxes will be dispatched stacked and ringed on **EURO-pallets**. This packing is a solution for a weight up to approx. 80 kg. gross per box.

For heavy commissions we provide a **systemized delivery on pallets**.

Based on a delivery of one packing unit per commission, each rope component package can easily be identified to the corresponding elevator. Sorting risks as well as loss of parts (for example accessories, during forwarding, in your warehouse, or on site) can be minimized by this **logistic service**. As an option bar code labels or labels according to your request can be added.

We are ready to assist in finding your best dispatch solution.



Warnings

Ropes must only be used in accordance with the applicable safety regulations and the relevant standards (DIN 15020, EN 12 385 and EN 81 and the German TRA).

If the installation is outside Germany the relevant statutory regulations and the national standards apply. Before usage inspect the rope and the rope terminations and comply with the recommendations of the manufacturer and the applicable standards.

Notes on breaking forces

The breaking strengths in the catalogue apply exclusively to new ropes. Whether the rope is performing as expected in the long run depends on

- The design of your elevator system
- The selected rope diameter
- The chosen rope construction
- The chosen rope grade and the
- Correct installation and maintenance of the elevator in which the rope is used, and
- The correct storage, handling, maintenance and inspection of the rope

Elevator Ropes

Tel. +49 (0) 208 429 010 Fax +49 (0) 208 429 0143

Inquiry **info.pmh@pfeifer.de**
 Order

to

PFEIFER DRAKO
Drahtseilwerk GmbH
 Rheinstraße 19-23
 45478 Mülheim an der Ruhr
 Germany

Customer-No.	Date
Company	
Ordered by	
Phone	Fax
E-Mail	

Order/Inquiry-No.:
Required delivery time:

Item 1 Traction drive ropes Hydraulic ropes

Pieces	Length in m	Ø mm	Construction	Price Euro

Item 2 1. Rope end

- plain end
- one end with ferrule secured thimble
- and attached eye bolt
 - M _____ with spring and accessories
 - with 1 PU-buffer and accessories
 - with 2 PU-buffer and accessories
 - with 3 PU-buffer and accessories
 - without any
- rope termination type _____ (loose)
- swaged fitting with thread M _____
- eye bolt M _____
 (quantity according to the number of the ropes)

Item 3 2. Rope end

- plain end
- rope termination type UM _____ (loose)
 (quantity according to the number of the ropes)

Item 4 _____ pieces of **rope grips** EN 13411-5 size _____

Item 5 _____ pieces of **Anti-Twist Rope Sets**

Item 6 Governor rope

Pieces	Length in m	Ø mm	Construction

- Item 7 Packing** Suspension Rope delivery in coils delivery on wooden reel
 Governor Rope delivery in coils delivery on wooden reel

Item 8 _____ pieces **wedge sockets** EN 13411-7 size _____

Item 9 _____ pieces of **rope grips** EN 13411-5 size _____

For ordering compensating ropes please use the order form 'Compensation' on page <ÜS>.

Delivery address (if different from order address):	Signature

Notes:

Deliveries according to the Terms of Delivery and Payment of PFEIFER DRAKO Drahtseilwerk GmbH

Compensation

Tel. +49 (0) 208 429 010 Fax +49 (0) 208 429 01 43

Inquiry **info.pmh@pfeifer.de**
 Order

to

PFEIFER DRAKO
Drahtseilwerk GmbH
 Rheinstraße 19-23
 45478 Mülheim an der Ruhr
 Germany

Customer-No.	Date
Company	
Ordered by	
Phone	Fax
E-Mail	

Order/Inquiry-No.
Required delivery time

Item 1 Compensating Chain (delivery always on wooden reels)	Pieces	Length	Price Euro
Type _____ Nom.-Ø in mm _____ Weight in kg/m _____			
Item 2 Installation Kit			
Type _____			
Item 3 Dampening Devices			
DR-L <input type="checkbox"/> DR-H <input type="checkbox"/>			
Item 4 Dismatling			
Type _____ Description _____ Length _____			
1-side <input type="checkbox"/> standard <input type="checkbox"/>			
2-side <input type="checkbox"/> 300 mm* <input type="checkbox"/>			
500 mm* <input type="checkbox"/>			
Item 5 Special Compensating Ropes			
Type _____ Ø in mm _____ Weight in kg/m _____			
Item 6 1. Rope end			
<input type="checkbox"/> plain end <input type="checkbox"/> one end with ferrule secured thimble <input type="checkbox"/> and eye bolt M _____ <input type="checkbox"/> with spring and accessories <input type="checkbox"/> with 1 PU-buffer and accessories <input type="checkbox"/> with 2 PU-buffers and accessories <input type="checkbox"/> with 3 PU-buffers and accessories <input type="checkbox"/> without any <input type="checkbox"/> rope termination type _____ loose <input type="checkbox"/> installation screw M _____ <input type="checkbox"/> swaged fitting with thread M _____			
Item 7 2. Rope end			
<input type="checkbox"/> plain end <input type="checkbox"/> rope termination _____ loose			
Item 8 Packing <input type="checkbox"/> delivery in coils <input type="checkbox"/> delivery on wooden reel			
Item 9 _____ pieces of rope grips EN 13411-5 size _____			
Delivery address(if different from order address):	Signature		

Comments

* not for WLC

Deliveries according to the Terms of Delivery and Payment of PFEIFER DRAKO Drahtseilwerk GmbH

Our delivery program

Elevator Industry

- Special ropes of 6-strand and 8-strand construction
- Special ropes with 9 outer strands for high rise/high speed installations
- Special compensating ropes
- Compensating chains and their suspension means
- Ropes for small goods elevators, overspeed controllers and door mechanisms



Bailong Elevator,
Wulingyuan, China



Accessories and Special Products

- Rope terminations
- Wire rope socks for cables and ropes
- Wire rope with polymer cover
- Spiral ropes and strands (automotive industry)
- Deep sea research ropes



Shaft Sinking

- Rotation resistant and non-rotating stage ropes
- Flat hoist ropes
- Clamshell ropes
- Guide ropes
- Direction survey ropes



Oilfield Industry

- Rotary drilling lines according to API Spec. 9A and DIN 5881
- Swab and bailing lines
- Winch lines
- Percussion drilling lines
- Air winch lines
- Logging lines and wires



Mechanical and Construction Industry

- Special crane and excavator ropes with 8 and 9 outer strands
- Rotation-resistant and non-rotating ropes for electric hoists
- Non-rotating ropes for tower cranes and mobile cranes
- Winch ropes, clamshell ropes and pendant ropes
- Slings according to DIN EN 13411-2/-3 and other slinging accessories

Mining

- Koepe hoist ropes
- Drum hoist ropes
- Flat hoist ropes
- Flat balance ropes
- Round balance ropes (multi-layer flat strand ropes)
- Haulage ropes for monorail conveyors

Notes







PFEIFER

PFEIFER DRAKO
Drahtseilwerk GmbH
Rheinstraße 19-23
45478 Mülheim an der Ruhr

drako.pfeifer.info
info.pmh@pfeifer.de

Sales Elevator Technology
Tel. +49 208 42901-0



Contact details of our global locations and sales partners can be found at

pfeifer.info/en/contacts/

Accreditations & Certifications



TÜV Süd

Germ. Lloyd

Lloyd's Register of Shipping

Quality management DIN EN ISO 9001

Envir. management DIN EN ISO 14001

Ecovadis Bronze

Energy management DIN EN ISO 50001

LOM Spain

GOST Russia

DRM Germany